

# theSEALERSTORE

## DSI (Injectable)

## Wood Deck

## Brightener-CA



1 Gallon (3.78 L)

#### DESCRIPTION:

Powersolve DSI Wood Brightener is a liquid concentrate that when injected through a pressure washer it brightens and restores the natural beauty of exterior wood. Powersolve Wood Brightener is essential after using Powersolve DSI Deck Stripper. It neutralizes and changes the pH balance of the wood to its natural state.

#### PREPARATION:

Powersolve DSI Deck Brightener may harm bare metal or painted surfaces. Pre-wet vegetation. Direct exposure may burn foliage but rinsing residue will not harm plants or roots.

#### APPLICATION PROCEDURES:

Apply Immediately after using DSI Deck Stripper. Use heavy duty rubber gloves. **Injector:** Attach Down Stream Injector to Pressure Washer and insert suction tube into gallon. Make sure product is flowing through tubing. You must use a chemical tip or wand. Apply sparingly at a ratio of 400-600 feet per gallon. The result should be immediate.

#### Wait:

Most applications will require a waiting period of approximately 5 to 15 minutes. Rinse when done.

#### PRECAUTIONS:

Danger: Keep out of the reach of children. Prolonged contact may cause burns. Avoid ingestion or contact with skin or eyes. Wear rubber gloves and goggles or safety glasses with side shields. Project surfaces are extremely slippery.

#### DISPOSAL:

Dispose remaining product in accordance with applicable environmental regulations. Neutralize with Powersolve Deck Stripper.

#### FIRST AID:

**Eyes:** This product is destructive to eye tissues on contact. Immediately flush eyes with large amounts of water for at least 15 minutes. SEEK MEDICAL ATTENTION IMMEDIATELY!

**Skin:** Immediately wash skin with large amounts of water. Remove contaminated clothing and shoes; wash before reuse. Get medical attention if irritation persists after washing.

#### HINTS:

Powersolve DSI Deck Brightener will brighten most species of wood. You should see an almost immediate result. A light rinse is suggested to remove any visible soap residue.

An injector with a ratio of 10:1 to 15:1 is best. Drain injector tubing when done.

Avoid any contact with aluminum or fiberglass siding or trim. A reaction may occur.

#### Distributed By:

OPW L.L.C./TheSealerStore.com  
1940 Star Batt  
Rochester Hills, MI 48309  
248-299-2512

#### Manufactured By:

CMI-Specialty Systems  
4520 Glenmeade Lane  
Auburn Hills, MI 48326  
248-340-0400

Contains: Citric Acid

**Emergency Phone Number**  
**1.800.424.9300**