

theSEALERSTORE

Wood Deck Stripper



1 Gallon (3.78 L)

TEST AREA:

Always prepare a test patch in an inconspicuous area prior to full application. This will indicate the performance and suitability of the product for the substrate.

PREPARATION:

Project surfaces must be dry and warm; above 50°F (10°C). Deck Stripper may harm bare metal or painted surfaces. Pre-wet vegetation. Direct exposure may burn foliage but rinsing residue will not harm plants or roots.

APPLICATION PROCEDURES:

Use heavy duty rubber gloves.

Gallon Container: Mix with water at 1:1 ratio. Apply with pump sprayer or bucket and scrub brush.

Wait:

Allow Powersolve Deck Stripper to soften or dissolve the coating. Most applications will require a waiting period of approximately 15 to 30 minutes. The coating residue should easily rinse off when ready. Multiple coatings may require more than application of Deck Stripper.

PRECAUTIONS:

Poison: Keep out of reach of children. Prolonged contact May cause burns. Avoid ingestion or contact with skin or eyes. Wear rubber gloves and goggles or safety glasses with side shields. Project surfaces are extremely slippery.

DISPOSAL:

Dispose remaining product in accordance with applicable environmental regulations. Neutralize with Deck Brightener.

Emergency Phone Number
1.800.424.9300

FIRST AID:

Eyes: This product is destructive to eye tissues on contact. Immediately flush eyes with large amounts of water for at least 15 minutes. SEEK MEDICAL ATTENTION IMMEDIATELY!

Skin: Immediately wash skin with large amounts of water. Remove contaminated clothing and shoes; wash before reuse. Get medical attention if irritation persists after washing.

HINTS:

Powersolve Deck Stripper will strip oil and common latex semi-transparent deck finishes. Scrub lightly where required. Use stiff brush or floor broom to help remove residue. Work in the direction of grain to minimize "grain raising" on wood surface. Rinse wood in direction of grain with water; using a garden hose or a 500-1200 PSI power washer. A power washer will eliminate the need for scrubbing.

Distributed By:

OPW L.L.C./TheSealerStore.com
1940 Star Batt
Rochester Hills, MI 48309
248-299-2512

Manufactured By:

CMI-Speciality Systems
4520 Glenmeade Lane
Auburn Hills, MI 48326
248-340-0400

Contains: Sodium Hydroxide

HEALTH: 2
FIRE: 0
REACTIVITY: 1